



ZPMV2.E301546 Wiring, Printed - Component

If you notice a change to your ZPMV2 Listing Card, click [here](#) to learn more.

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

ALLFAVOR CIRCUITS (SHENZHEN) CO LTD

E301546

Bldg A4
Yanchuan Northern Industrial Park
Bao'An District, Songgang Town
Shenzhen, Guangdong 518105 CHINA

	Cond Width		Cond	SS/ DS/	Max Area	Solder		Max Oper	Meets	C	
	Min	Edge				Thk	Limits				Temp
Type	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
Multilayer printed wiring boards.											
AF-M1	0.1 (0.004)	0.1 (0.004)	17 (0.67) Int:68	DS	76.2 (3.0)	288	20	130	V-0	All	3
AF-M2(NOTE 1)											
	0.1 (0.004)	0.1 (0.004)	17 (0.67) Int:204	DS	76.2 (3.0)	288	30	130	V-0	All	*
Single Layer Metal Base printed wiring boards.											
AF-A1	0.20 (0.008)	0.20 (0.008)	35 (1.38)	SS	76.2 (3.0)	288	20	130	V-0	All	-
AF-A2	0.20 (0.008)	0.60 (0.024)	35 (1.38)	SS	76.2 (3.0)	288	20	130	V-0	-	-
AF-A3	0.20 (0.008)	0.60 (0.024)	17.5 (0.69)	SS	76.2 (3.0)	288	20	130	V-0	-	-
Single layer printed wiring boards.											
AF-D1	0.10 (0.004)	0.10 (0.004)	17 (0.67)	DS	76.2 (3.0)	288	20	130	V-0	All	3
AF-D2(NOTE 1)											
	0.1 (0.004)	0.1 (0.004)	17 (0.67)	DS	76.2 (3.0)	288	30	130	V-0	All	*
AF-T1	0.20 (0.008)	0.20 (0.008)	35 (1.38)	DS	76.2 (3.0)	265	5	150	V-0	All	0
Single layer printed wiring boards, flammability only Recognition.											
AF-R1	-	-	-	DS	-	288	20	-	V-0	-	-

(NOTE 1) - Min. Cond. Width and Min. Edge Cond. Width is 0.10mm when External Cu Thk. is 17-102 mic. Min. Cond. Width and Min. Edge Cond. Width is 0.30mm when External Cu Thk is 102-204 mic.

* - CTI marking is optional and may be marked on the printed wiring board.

ALLFAVOR

Marking: Company name or tradename "E301546" or trademark identification or burning test classification.

[Last Updated](#) on 2017-09-05

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".